

BOARD OF DIRECTORS

Geoff English
President

Navid Fardanesh
Vice-President

Pamela Jardini
Director

Debra Logan
Director

Wayne Petersen
Director



STAFF

Jeff Britz
General Manager

Bettina L. Mayer, P.E.
District Engineer

Laurie A. Ion
Assistant to GM/
Board Secretary

Frank Sprague
Utilities Manager

Natalie Klock
Finance Officer

Bill White
Fire Chief

Melissa Johnson
Recreation Supervisor

TEMPLETON COMMUNITY SERVICES DISTRICT

P.O. BOX 780 • 420 CROCKER STREET • TEMPLETON, CA 93465 • (805) 434-4900 • FAX: (805) 434-4820
www.templetoncsd.org

Water Supply Sources Overview

DATE: Updated January 23, 2020

FROM: Bettina L. Mayer, PE, District Engineer

The District relies on a combination of several different water sources to provide a sustainable water supply to its customers. Water sources include deep aquifer groundwater, shallow underflow water, and water supply augmentation through treated wastewater retrieval and importation of Nacimiento raw water. The water enters the water system through 12 wells, all located within the Templeton Subunit of the Atascadero Basin.

The Atascadero Subbasin has a distinct hydraulic separation from the Paso Robles Subbasin at the Rinconada fault as defined in the Paso Robles Groundwater Basin Study prepared by Fugro in 2002, and subsequent studies. The portion of the Atascadero Basin underlying District wells, informally named the Templeton Subunit, has been further evaluated by FUGRO, the District's hydrogeologist, in its August 2013 updated report titled 'Updated Templeton Subunit Study'. The aquifer contains two primary water-bearing geologic units: the Paso Robles Formation, and the Salinas River alluvial gravels. The deep, percolating groundwater wells located within the Paso Robles Formation are generally referred to as 'deep' wells, and wells extracting the underflow from the Salinas River alluvial gravels are referred to as the 'river' wells.

The water supply sources are further described below:

Percolating Ground Water -Deep Wells

The District extracts percolating groundwater from 9 active deep wells located throughout the District. FUGRO recently completed a study of the District's deep aquifer supply capability and concluded that a perennial yield of 1040 acre-feet per year (AFY) may be used as an operational guide for the 9 deep wells. This water is available year round, however these wells are used primarily to meet summer demands.

Salinas Underflow -River Wells

The District has three river wells that divert water from the Salinas River underflow. The District relies primarily on two river wells, the Smith River well, and the Creekside River Well. The third river well is currently a standby emergency well only.

The District has several water rights for diversions of water from the Salinas River underflow that includes two State Water Resources Control Board water permits and one water license. The District also has several riparian rights agreements by which it provides water to customers through its system and pumps the same amount of water from the underflow. All together, the underflow water supply totals approximately 690 AFY.

Treated Wastewater Retrieval (also may be called Underflow Augmentation)

The District discharges treated wastewater into discharge ponds (Selby ponds) located adjacent to the Salinas River where it is percolated into the underflow of the Salinas River. The water may be retrieved, less 2%, 28 months later at the Smith River Well, or 35 months later at the Creekside River Well. In 2019 the District completed a major wastewater infrastructure project call the East Side Force Main and Lift Stations (ESFM) which increased the total wastewater flows to the Meadowbrook Wastewater Treatment Plant (MWWTP) from approximately 150,000 gallons per day (gpd) to an average of 438,000 gpd. Once 100% of these flows are available for discharge into the Selby ponds, a total of 480 AFY of water will be available from this source annually. Due to the locations of the two wells, all of the water discharged at the Selby ponds can be retrieved during the summer pumping season from April through October.

Nacimiento Water

The District began receiving 250 AFY of raw Nacimiento water deliveries on June 23, 2011. An additional 156 AFY of 400 AFY annually. The Nacimiento water supplements the water supply during the peak summer Nacimiento water was purchased 2016. Until March of 2019, the raw water was percolated into the underflow at the Selby ponds for subsequent retrieval downstream at the Smith Well and Creekside Wells. Retrievals from Nacimiento discharges will end in 2022. The District is in the planning stages of relocating the Nacimiento water to another site and it is anticipated that this project could be on line as early as 2027. Once the Nacimiento water becomes available the District will net approximately season and provides some additional source capacity for the District.

Current Supply

The District's 2020 available water supply from all sources is approximately 2142 AFY. Actual water use peaks in July and August when outdoor use is greatest and it can be over three times winter water use. At this time, the District is capable of meeting the seasonal average daily water demands of the District.

As additional wastewater is percolated and subsequently available for retrieval, the amount of water supply will increase. The next largest water supply increase will be realized once a new Nacimiento water delivery location and infrastructure is planned and constructed.